





StreetLighting







- Upgrade to LED while keeping the existing fixture
- Active cooling fan >70,000hr rated life
- Maintenance free
- Upgradeable solution
- Ouick return on investment

360°

Specification (±2% range)

Replaces: 50-70W SON / HPS Input voltage: 120-277 VAC -40° C - $+50^{\circ}$ C Power consumption: 18W Operating temp: CCT: 4000K Rated R70 life: Up to 50,000 Hrs. CRI: >84.7 Dimmable: Lumen output: 2.297 Mounting:

Beam angle: **UMSUG Code:** 42 0019 0000 100 Efficacy: 128

> Designed for fully enclosed fixtures www.mallatite.co.uk/certificates-warranty

160mm x 63mm x 63mm



When installing the retrofit lamp within HID fixtures, the ballast must be bypassed when present.

The LED lamps are UL damp rated, sealing the fixtures after installation will deliver best results.

Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations

Dimensions:



Mallatite Ltd operates a policy of continuous product development and reserves the right to change or improve specification without prior notice. E & OE. © 2017 Mallatite Ltd All Rights Reserved. Company No. 2621328 VAT Registration No: GB 561200488 Registered Office: Hill & Smith Holdings Plc. Westhaven House Arleston Way, Shirley, Solihull, West Midlands, England, B90 4LH Version 05/06/17